

IMPORTANT INFORMATION

**PLEASE READ INSTRUCTIONS CAREFULLY,
FAILURE TO COMPLY MAY VOID YOUR WARRANTY**

1. LEAVE THE HOSE RUNNING CONTINUOUSLY, **DO NOT MOVE THE HOSE OR TURN THE HOSE OFF** UNTIL THE WATER IS HALF WAY UP THE SKIMMER BOX.
2. IF YOU FEEL THE NEED TO **ADD ADDITIONAL HOSES** YOU MUST WAIT UNTIL THE **FLOOR IS COMPLETELY COVERED IN WATER**, THEN INSERT THE HOSE DIRECTLY INTO THE DEEP END ONLY. **DO NOT** RUN THE WATER DOWN THE WALL OF THE POOL OR LEAVE PUDDLES ON THE STEPS OR LEDGES AS YOU WILL CAUSE STAINING.
3. ONCE THE FLOOR OF THE POOL IS APPROXIMATELY HALF FULL WITH WATER, **ADD A CALCIUM INHIBITOR** TO LIMIT THE POTENTIAL FOR SCALE TO BUILD-UP.
4. **DO NOT ENTER THE POOL** OR WALK ON THE FRESH RENDER FOR A MINIMUM OF 36 HOURS.
5. **AFTER 18-24 HOURS** TURN ON THE FILTRATION AND CHECK THE PH LEVELS, IN MOST CASES YOU WILL NEED TO ADD ACID, DO SO IF REQUIRED.
6. GIVE THE WALLS AND FLOOR A **LIGHT BRUSH DOWN AT LEAST ONCE OR TWICE EACH DAY** FOR THE **FIRST 14 DAYS** THIS WILL HELP REMOVE ANY SEDIMENT BUILD UP.
7. **DO NOT** USE YOUR AUTOMATIC POOL SURFACE CLEANER VACUUM WITHIN THE **FIRST 5 DAYS**.
8. **DO NOT** ALLOW LEAVES, DIRT, WOOD CHIP, PINE BARK OR CONTAMINANTS OF ANY KIND TO SIT ON THE INTERIOR AS STAINING CAN OCCUR AND BECOME DIFFICULT TO REMOVE.
9. IF THE POOL IS A SALT WATER POOL **DO NOT ADD SALT** FOR THE **FIRST 14 DAYS**. ENSURE ALL CHEMICALS ARE DISPERSED INTO THE POOL AND NOT LEFT TO SIT UNDISSOLVED ON THE INTERIOR SURFACE.

Please refer to the general start-up information for further details available to download from www.gemtex.com.au. Seek advice from a pool care professional or your pool builder if you are unfamiliar with water balancing.

1300 GEMTEX (1300 436 839)

www.gemtex.com.au